Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-29. (canceled)

- 30. (currently amended) The section claimed in claim

 47electrical wiring trunking claimed in claim 43, wherein each hole precursor is a blind hole whose bottom is constituted by a continuous web.
- 31. (previously presented) The section claimed in claim 47 wherein at least one of said hole precursors has an oblong shape.
- 32. (canceled)
- 33. (currently amended) The section claimed in claim 47
 electrical wiring trunking claimed in claim 43, wherein each
 hole precursor is a through-hole surrounded by a continuous
 annular web.

- 34. (previously presented) The section claimed in claim 33 wherein the hole precursor has an oblong shape.
- 35. (canceled)
- 36. (currently amended) The section claimed in claim 47
 electrical wiring trunking claimed in claim 43, wherein each
 hole precursor is a closed contour formed by a succession of
 blind openings along the periphery of the hole.
- 37. (previously presented) The section claimed in claim 36 wherein the hole precursor has an oblong shape.
- 38. (canceled)
- 39. (currently amended) The section claimed in claim 47 An electrical wiring trunking comprising a cover and a base portion, said base portion being constituted by a thermoplastics material section having a U-shaped cross section and comprising a wall having two longitudinal edges and two flanges each extending transversely to said wall and each joined to a respective longitudinal edge of said wall, wherein:

weakened areas, each mechanically weakened area being a precursor for a hole having a closed periphery, and wherein—each hole precursor is a closed contour formed by a succession of through-openings located along the periphery of the hole.

- 40. (previously presented) The section claimed in claim 39 wherein the hole precursor has an oblong shape.
- 41. (canceled)
- 42. (previously presented) The section claimed in claim 47 wherein each hole precursor has an oblong shape.
- 43. (previously presented) An electrical wiring trunking comprising a cover and a base portion constituted by a thermoplastics material section according to claim 47.
- 44. (currently amended) The section claimed in claim 47
 electrical wiring trunking claimed in claim 43, wherein each
 hole precursor is a closed contour formed by a groove.

45. (currently amended) An electrical wiring trunking comprising a base portion constituted by a plastic material section according to claim 47, wherein each at least some of said hole precursors is are adapted to receive a fixation screw.

46. (canceled)

47. (currently amended) A thermoplastics material section having a U-shaped cross section and comprising a wall having two longitudinal edges and two flanges each extending transversely to said wall and each joined to a respective longitudinal edge of said wall, wherein:

said section contains a longitudinal succession of mechanically weakened areas, each mechanically weakened area being a precursor for a hole having a closed periphery; and at least one of said precursors consists of one of:

- a blind hole whose bottom is constituted by a continuous web;
- a through-hole surrounded by a continuous annular web; and
- a closed contour formed by a groove, or by a succession of blind openings or by a succession of through openings located along the periphery of the hole.

48. (previously presented) The section claimed in claim 47 wherein said longitudinal succession of mechanically weakened areas is provided in said wall.